



GS-5124C

GS-5124C:

24-Port Unmanaged Gigabit Ethernet Switch

Key Features

- 24-Port 10/100/1000 Mbps GbE Switch
- Provides two Gigabit Ethernet Modules options: 1000Mbps RJ-45/1000Mbps Fiber SFP (single-mode/multi-mode) for remote uplink • Conforms to IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3ab 1000BASE-T and IEEE 802.3x flow control standards
- Supports 10/100Mbps auto-detect half/full duplex and 1000Mbps at full duplex
- Supports TP interface auto MDI/MDI-X function for auto TX/RX swap
- Supports 802.3x flow control pause packet for full duplex
- LEDs to indicate: 10/100/1000Mbps, Link /Act. and Power Status
- Slim & Compact design
- RoHS Compliance

Overview

GS-5124C is a cost-effective switch that meets all IEEE 802.3/u/x/z Gigabit, Fast Ethernet specifications. With 48 Gbps switch fabric, the switch improves your network performance. You can connect to backbone or make Gigabit to the PC to perform high speed transfer. The switch has a 8K MAC Address Table and provides a 400K on-chip buffer. It is suitable for workgroups or WAN edge application. The versatile and compact 1RU height design of the **GS-5124C** enables the device to be rackmounted in a standard 19 inch rack, while conserving valuable rack space.

Easy Installation and Configuration

GS-5124C conforms to plug and play for easy installation and use. With diagnostic LEDs, network and port status can be easily monitoring and trouble-shooting.

GS-5124C also build in wiring crossover on all ports allows connection to server or PC without worrying about cabling.

Technical Specifications

- **Standard compliance:**
 - IEEE 802.3 10Base-T Ethernet (twisted-pair copper)
 - IEEE 802.3u 100Base-TX Ethernet (twisted-pair copper)
 - IEEE 802.3ab 1000Base-T Ethernet (twisted-pair copper)
 - IEEE 802.3Z 1000Base-T Ethernet (Gigabit Fiber)
 - ANSI/IEEE 802.3 Auto-negotiation
- **MAC Address:** 8K
- **Network Interface:** 24 10/100/1000Mbps RJ-45 ports
- **Flow control:**
 - IEEE802.3x compliant for full-duplex
 - Back pressure flow control for half-duplex
- **Media:**
 - 10BASE-T: UTP Cat. 3, 4, 5 or up
 - 100BASE-TX: UTP Cat. 5 or up
 - 1000BASE-T: UTP Cat. 5 or up
- **Transmission Mode:** 10/100Mbps, full/half-duplex (Auto-sensing)
- **Transfer Rate:**
 - 10Mbps: 14880pps (64 Bytes Package)
 - 100Mbps: 148800pps (64 Bytes Package)
 - 1000Mbps: 1488000pps (64 Bytes Package)
- **Buffer Memory:** 400KB on chip frame buffer
- **Switching Method:** Store & forward
- **LED Description**

| | LED | Color | Function |
|-----------|--------------|-------------|--|
| Global | POWER | Green | Lit when +5V power is coming up |
| Global | CPU/ACT | Green | Blinks when CPU is activity |
| Port 1-24 | LINK/ACT | Green | Lit when connection with remote device is good Blinks when any traffic is present |
| Port 1-24 | 1000/100Mbps | Green/Amber | Lit Green when TP link on 1000Mbps speed Lit Amber when TP link on 100Mbps speed |
| | | | Off when 10Mbps or no link occur |

• Hardware Spec.

| Feature | Detailed Description |
|----------------------------|--|
| Voltage | 100~240 V |
| Frequency | 50~60 Hz |
| Consumption | 30W |
| Ambient Temperature | 0 to 40 °C |
| Humidity | 5% to 90% |
| Dimensions | 44(H) x 442(W) x 209(D) mm |
| Weight | 3kg |
| Safety | UL Comply with FCC Part 15 Class A & CE Mark Approval |

Packing Information

| Carton Dimensions (mm) | pcs/Carton | N.W (KG) | G.W (KG) |
|------------------------|------------|----------|----------|
| 530x512x345 | 5 | 20 | 21 |

Ordering Information

| | |
|----------------------------|--|
| GS-5124C | 24-Port Unmanaged Gigabit Ethernet Switch with 2 SFP Dual Media Port |
| Optional SFP Module | |
| SFP.LC | 1000Base-SX GE SFP Fiber Module, LC Multi-Mode 850nm |
| SFP.LC.M2 | 1000Base-SX GE SFP Fiber Module, LC Multi-Mode 1310nm 2km |

Note:

We recommend the SFP transceiver from the following vendors:

1. Ruby Tech Corporation
2. Agilent Technologies
3. AVAGO Technologies
4. Finisar Corporation

Ruby Tech Corp.

3F, No.1, Lane 50, Nan Kang Road, Sec.3, Taipei, Taiwan
 TEL:886-2-2785-3961 FAX:886-2-2786-3012

<http://www.rubytech.com.tw>
 E-mail : rubytech@mail.rubytech.com.tw